



When you need a High Quality Opening

Alfa Laval Access Tank Cover - Circular Cover Type LKDS

Application

The circular LKDS stainless steel manhole cover is used on top of tanks or containers where a closeable mean of access to the interior of the tank is required, and is especially suitable for dairy balance tanks and CIP holding tanks.

Working principle

The LKDS cover is not designed to fit watertight to the tank and therefore it is supplied with a splash guard to prevent liquid spraying out during a cleaning process.



TECHNICAL DATA


Working pressure: No pressure

Certificates

3.1 certificate

Dimensions (inch)

Size/OD	454	454
ID	17.64	17.64
F	0.94	3.94
t	0.12	0.12
C	10.71	10.71
Cover thickness	0.08	0.08



PHYSICAL DATA

Materials

Lid and frame: 1.4301 (304) or 1.4404 (316L)

Surface finish: Acid Pickled

Product wetted surfaces: Ra 32µin

Other surfaces: Ra 120µin

Temperature

Min. temperature: - 4°F

Max. temperature: + 194°F

Weight: 11 / 13.2 lbs.



Alfa Laval reserves the right to change specifications without prior notification. ALFA LAVAL is a trademark registered and owned by Alfa Laval Corporate AB.

ESE00315ENUS 1507

© Alfa Laval

How to contact Alfa Laval

Contact details for all countries are continually updated on our website. Please visit www.alfalaval.us to access the information direct.